



Safety Data Sheet
according to Regulation (EC)
No. 2020/878

SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product Identifier	NC07Z900	Revision Date:	05/06/2023
Product Name:	THERMO-LAG 3000-P PART B	Supersedes Date:	16/03/2022
		Version Number:	3

UFI Code: 9RK0-N01N-R00X-11AH

Nano Form: No

1.2 Relevant identified uses of the substance or mixture and uses advised against

Hardener for 2 components coatings - Industrial use.
Advised against: others than recommended
Fireproofing material.
Advised against: Home DIY applications.

Product to be mixed with: THERMO-LAG 3000-P PART A
**Mixing ratio by volume Part A/
Part B:** 1:1

1.3 Details of the supplier of the safety data sheet

Manufacturer: Carboline Norge AS
Postboks 593
3412 Lierstranda
Norway

Regulatory / Technical Information:
+47 32 85 73 00
+47 32 85 74 00

Datasheet Produced by: Tarka, Malgorzata - hms@carboline.com

1.4 Emergency telephone number: CHEMTREC +1 703 5273887 (Outside US)
112 (24/7)
Croatia +3851 2348 342 (24/7 in Croatian and English)
Iceland 112 (24/7)
Malta 112 (24/7)

SECTION 2: Hazards Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Skin Irritation, category 2

H315

Serious Eye Damage, category 1	H318
Hazardous to the aquatic environment, Chronic, category 3	H412

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

((dimethylamino)methyl)phenol

HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Serious Eye Damage, category 1	H318	Causes serious eye damage.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.

PRECAUTION PHRASES

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P332+313	If skin irritation occurs: Get medical advice/attention.
P501	Dispose of contents/container to waste treatment/disposal facility in accordance with local, state, and federal regulations.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

Endocrine disrupting properties - Toxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

Endocrine disrupting properties - Ecotoxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 3: Composition/Information On Ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous ingredients

<u>Name According to EEC</u> <u>EINECS No.</u> <u>CAS-No.</u> <u>REACH Reg No.</u>	<u>%</u>	<u>Classifications</u>	SCL Value ATE Value M-Factor	
aliphatic polysulfid-polymer 614-671-8 68611-50-7 -	25 - <50	H412 Aquatic Chronic 3	SCL: ATE: M-Factor:	- - -
((dimethylamino)methyl)phenol - 25338-55-0 01-2120810854-55	2.5 - <10	H302-314-332 Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Skin Corr. 1C	SCL: ATE: M-Factor:	- - -
glass oxide 266-046-0 65997-17-3 -	2.5 - <10		SCL: ATE: M-Factor:	- - -
Siloxanes and Silicones, di-Me, reaction products with silica 614-122-2 67762-90-7 -	1.0 - <2.5		SCL: ATE: M-Factor:	- - -

carbon 231-153-3 7440-44-0 -	1.0 - <2.5		SCL:	-
			ATE:	-
			M-Factor:	-
phenol 203-632-7 108-95-2 01-2119471329-32	0.1 - <1.0	H301-311-314-331-341-373 Acute Tox. 3 Dermal, Acute Tox. 3 Inhalation, Acute Tox. 3 Oral, Muta. 2, Skin Corr. 1B, STOT RE 2	SCL:	H314 ≥ 3 H315 ≥ 1 H319 ≥ 1
			ATE:	-
			M-Factor:	-
2,4,6-tris(dimethylaminomethyl) phenol 202-013-9 90-72-2 01-2119560597-27	0.1 - <1.0	H302-314-318 Acute Tox. 4 Oral, Eye Dam. 1, Skin Corr. 1C	SCL:	-
			ATE:	2 169 mg/kg (oral)
			M-Factor:	-

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Move to fresh air. Give oxygen or artificial respiration if needed. When risk of unconsciousness, place and transport the victim in secured recovery position. Provide fresh air, rest and warmth. Call a physician immediately.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do not use solvent or thinners to clean skin.

AFTER EYE CONTACT: Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. Causes serious eye damage.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Immediate medical attention is required.

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5: Firefighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

Do not use a solid water stream as it may scatter and spread fire.

5.2 Special hazards arising from the substance or mixture

Heating or fire conditions liberates toxic gas. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Keep containers and surroundings cool with water spray.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents.

6.4 Reference to other sections

Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Open drum carefully as content may be under pressure. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used. Apply technical measures to comply with the occupational exposure limits (see section 8).

Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid heat, sparks, flames and other ignition sources.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in upright position only. Store away from: oxidising materials, acids, and alkalis.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
aliphatic polysulfid-polymer	68611-50-7				
((dimethylamino)methyl)phenol	25338-55-0				
glass oxide	65997-17-3				
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7				
carbon	7440-44-0				
phenol	108-95-2	2	4	16	8
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2				

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
aliphatic polysulfid-polymer	68611-50-7	
((dimethylamino)methyl)phenol	25338-55-0	
glass oxide	65997-17-3	
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	
carbon	7440-44-0	
phenol	108-95-2	
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

Chemical Name:

glass oxide

EC No.:

266-046-0

CAS-No.:

65997-17-3

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							
Inhalation								
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	6.5 µg/L
Fresh water sediments	174 mg/kg sediment dw
Marine water	3.4 µg/L
Marine sediments	164 mg/kg sediment dw
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	147 mg/kg soil dw
Air	

Chemical Name:

phenol

EC No.:

203-632-7

CAS-No.:

108-95-2

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							0.4 mg/kg
Inhalation	16 mg/m3			8 mg/m3				1.32 mg/m3
Dermal				1.23 mg/kg				0.4 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.008 mg/L
Fresh water sediments	0.091 mg/kg
Marine water	0.001 mg/L
Marine sediments	0.009 mg/kg
Food chain	
Microorganisms in sewage treatment soil (agricultural)	0.136 mg/kg
Air	

Chemical Name:

2,4,6-tris(dimethylaminomethyl)phenol

EC No.:

202-013-9

CAS-No.:

90-72-2

DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required					0.13 mg/m3		0.075 mg/kg
Inhalation		2.1 mg/m3	4.9 mg/m3	0.53 mg/m3		0.075 mg/kg		0.13 mg/m3
Dermal		0.6 mg/kg		0.150 mg/kg				0.075 mg/kg

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.046 mg/l
Fresh water sediments	
Marine water	0.005 mg/l
Marine sediments	
Food chain	
Microorganisms in sewage treatment soil (agricultural)	0.2 mg/l
Air	0.025 mg/kg

8.2 Exposure controls**Personal Protection**

RESPIRATORY PROTECTION: Use compressed air or fresh air breathing apparatus in closed compartments. Wear respiratory protection with combination filter (dust and gas filter, EN 14387:2004+A1:2008) during spraying operations: Gas filter type A2 (organic substances). Dust filter P3 (for fine dust). When working in confined or poorly ventilated spaces, a battery powered assisted air-fed mask must be used.

EYE PROTECTION: Face-shield.

HAND PROTECTION: Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Use chemical resistant gloves and lotions and barrier creams to prevent drying of the skin. Protective gloves complying with EN 374: Butyl rubber. Nitril rubber. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber.

OTHER PROTECTIVE EQUIPMENT: Protective suit. Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Colour	Black viscous liquid
Physical State	Liquid
Odor	Mercaptan
Odor threshold	Not determined
pH	Not determined
Melting point / freezing point (°C)	Not determined
Boiling point or initial boiling point and boiling range (°C)	83 - 316
Flash Point, (°C)	93
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Lower and upper explosive limit	Not determined
Vapour Pressure	Not determined
Relative vapour density	>1 (air = 1)
Density and/or relative density	1.20 - 1.38
Solubility in / Miscibility with water	Negligible
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Kinematic viscosity	120,000 - 200,000 cP
Particle characteristics	Not applicable to liquids

9.2 Other information

VOC Content g/l:	13
------------------	----

Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.

Specific Gravity (g/cm ³)	1.49
---------------------------------------	------

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under recommended storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No reactivity hazards known under recommended storage and use conditions.

10.4 Conditions to avoid

Avoid heat, sparks, flames and other ignition sources.

10.5 Incompatible materials

Avoid radical-forming starting agents, peroxides and reactive metals. Keep away from strong oxidising agents and strongly acid or alkaline materials.

10.6 Hazardous decomposition products

Ammonia gas may be liberated at high temperatures. In case of fire or hot work operations, hazardous decomposition products may be formed such as: Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), aliphatic amines, phenol, aldehydes. Sulphur oxides. Hydrogen sulphide.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute Toxicity:

Oral LD50:	No information available on the product itself as the product is not tested.
Inhalation LC50:	No information available on the product itself as the product is not tested.
Dermal LD50:	No information available on the product itself as the product is not tested.

Irritation: Irritating to skin.

Corrosivity: Causes serious eye damage.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.
Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
25338-55-0	((dimethylamino)methyl)phenol	1500 mg/kg	>2000 mg/kg	15 mg/L (vapour)	No information	No information
65997-17-3	glass oxide	>2000 - 5000 mg/kg bw (rat)	No information	No information	No information	No information
67762-90-7	Siloxanes and Silicones, di-Me, reaction products with silica	6350 mg/kg (oral-rat)	>2000 mg/kg (dermal-rat)	No information	No information	No information
108-95-2	phenol	300 mg/kg oral	630 mg/Kg (Dermal, rabbit)	316 mg/m ³ inhalation	No information	No information
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	2169 mg/kg (oral, rat)	No information	No information	No information	No information

Additional Information:

Corrosive - causes irreversible eye damage. Chronic exposure causes drying effect on the skin and eczema. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Chronic exposure has been associated with various neurotoxic effects including permanent brain damage. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs.

11.2 Information on other hazards

Endocrine disrupting properties - Toxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

SECTION 12: Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

12.2 Persistence and degradability: Not readily biodegradable

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment: The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

12.6 Endocrine disrupting properties

Endocrine disrupting properties - Ecotoxicity

Based on the available data, the product does not contain substances identified as having endocrine disrupting properties according to Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in concentration of 0,1% or higher.

12.7 Other adverse effects: No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
68611-50-7	aliphatic polysulfid-polymer	4.71 mg/L	17 mg/L	320 mg/L
65997-17-3	glass oxide	No information	1000 mg/L	1000 mg/L
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	718 mg/L (EC50, 96h, Palaeomonetes vulgaris)	84 mg/L (EC50, 72h, Desmodesmus subspicatus)	175 mg/L (LC50, 96h, Cyprinus carpio)

SECTION 13: Disposal Considerations

13.1 **WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Empty containers should be taken to an approved waste handling site for recycling or disposal. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

European Waste Code: 08 01 11*

Packaging Waste Code: 15 01 10*

SECTION 14: Transport Information

	ADR/RID	ADN	IMDG	IATA
14.1 UN-number or ID number	Not applicable	Not applicable	Not applicable	Not applicable
14.2 UN proper shipping name	Not regulated	Not regulated	Not regulated	Not regulated
14.3 Transport Hazard Class(es)	Not applicable	Not applicable	Not applicable	Not applicable
14.4 Packing Group	Not applicable	Not applicable	Not applicable	Not applicable
14.5 Enviromental Hazards	Not applicable	Not applicable	Not applicable	Not applicable

14.6 Special precautions for user No Information

EmS-No.: No Information

14.7 Maritime transport in bulk according to IMO instruments No Information

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number: Not available

Danish MAL Code: Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number: Not available

WGK Class: 3

Covered by Directive 2012/18/EC (Seveso III): Not applicable

Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006: Entry 3

Annex XIV - Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

<u>CAS-No.</u>	<u>Name According to EEC</u>
----------------	------------------------------

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

<u>CAS-No.</u>	<u>Name According to EEC</u>
----------------	------------------------------

Not Applicable

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information**Text for CLP Hazard Statements shown in Section 3 describing each ingredient:**

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes. .

List of References

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark
- Joint Research Centre in Ispra, Italy
- Regulation (EC) 1272/2008 with subsequent amendments
- Regulation (EC) 1907/2006 with subsequent amendments
- Commission Regulation (EU) 2020/878
- Eu Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value

ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects
IMO	International Maritime Organization
Note P:	The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene
Note 10:	The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

For further information, please contact: Regulatory Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.